



BS 2TMY

Seismic Earthquake Sensor



It detects earthquake motion in seismic tremors at the acceleration value specified in TSE (Turkish Standards Institute) Standards. It has internal battery and relay output. In case of disaster, you can cut off the electricity or have the siren sound.

DIMENSIONS

Width : 210mm

Height : 170mm

Depth : 60mm

MEASUREMENT

Measurement Range Temperature Range: 0 / +51.5 °C

Relative Humidity: 0-90%

BATTERY

Battery Capacity : 12V 1,3 Ah

Battery Working Time : 36 Hours

MOUNTING

Wall Mount

MONITORING & MANAGEMENT SOFTWARE

Sensaway Monitoring & Management Software

WEIGHT

2 kg

TECHNICAL SPECIFICATIONS

Operating Voltage: 100-260 VAC (50-60 Hz)

Relay Contact Output: 230 VAC 5A

Solenoid Valve Relay Output: 1A-12V DC

Maximum Impact Acceleration Withstand: 50,000g

ALERT, WARNING & NOTIFICATION

Written and illuminated warning via LCD (*1)

Email (with management software)

SMS and Phone Call (with SMS Module)

Audible alert via management software

Audible - Visual warning module (siren)(*2)

Sensaway Mobile App Notification

(*1) It works with BirSens modules.

(*2) It works with compatible BirSens modules & Siren.