



BS 865T

Central SMS and Call Module



Be Informed in Critical Situations

In case the sensor parameters in the environment go beyond the threshold values you have determined; it notifies the authorized persons by SMS and call. Since it communicates directly with Sensaway software, it provides management and cost advantages in multiple locations with a single device and sim card

GENERAL FEATURES

- Common solution for all locations on the same network
- Sensaway software communication via USB (server)
- Sending SMS or calling to unlimited number of users.
- LED indicators showing instant situation: Power - GSM



TECHNICAL SPECIFICATIONS

BS 865T

DIMENSIONS

Height: 32mm

Width: 82mm

Depth: 84mm

WEIGHT

200 g.

ELECTRICITY AND OPERATING REQUIREMENTS

-40°C +85°C & 0 – 85 % RH Humidity

Power: 5 Volt

MODEM FEATURES

RS232-USB

Band: 800/500, 900 AWS 1700, 1900, 2100

CONNECTIONS

USB Port

Standard Size Sim Card Slot

MOUNTING

Wall Mount

Desktop Mount

MONITORING & MANAGEMENT SOFTWARE

Sensaway Management & Monitoring Software

STATUS DISPLAY

2 Status led

ACCESSORIES

Installation Guide

5V DC Adapter

External GSM Antenna