



BS 978T

Central Smart SMS and Call Module



Be Informed in Any Situation

In case the sensor parameters in the environment go beyond the threshold values you have determined; it notifies the authorized persons by SMS and call. Since it communicates directly with Sensaway software, it provides management and cost advantages in multiple locations with a single device and sim card.

GENERAL FEATURES

- Common solution for all locations on the same network
- Notification in case of power cuts thanks to the built-in 6-hour battery / storage battery support
- Sensaway software communication over Ethernet (IP)
- Ability to be managed over the Web
- Send notification in case of sabotage or when Sensaway software is not running
- SMS or call an unlimited number of users
- LED indicators showing instant situations:
Power - Wireless - GSM - Sensaway- Ethernet



TECHNICAL SPECIFICATIONS

BS 978T

DIMENSIONS

Height: 48mm

Width: 205mm

Depth: 145mm

WEIGHT

270 g.

ELECTRICITY AND OPERATING REQUIREMENTS

-40°C, +85°C & 0 – 85 %RH Humidity

Power: 5 Volt

MODEM FEATURES

Telit HE/UE 910 3G Modem

Band: 800/500, 900 AWS 1700, 1900, 2100

CONNECTIONS

100Mbps ethernet LAN/WAN

Standard Size Sim Card Slot

MOUNTING

Wall Mount

Desktop Mount

BATTERY

Battery Type: Power Xtra PX503450

Capacity: 3.7V 900 mAh Li-Polymer

MONITORING & MANAGEMENT SOFTWARE

Sensaway Monitoring & Management Software

STATUS DISPLAY

5 Status Led

ACCESSORIES

Installation Guide

5V DC Adapter

External GSM Antenna

NETWORK AND SECURITY

10/100 Ethernet

Password Protection, IP Address Filtering

