



IP CAMERA

IP Camera with Motion Detection and Sensaway License



(Management Software Screen)



You Don't Need To Watch Constantly

Since it detects motion instead of recording continuously, it takes pictures at desired intervals and saves them on the Sensaway software server. When you enter the room, the official e-mail of the person entering the room is sent to the authorized persons. You can see who comes in and who leaves the room at the time intervals you specify, with their pictures on the Sensaway software.

GENERAL FEATURES

- Comply with ONVIF Standards
- IP67 protection class
- POE energy powered
- 20 meters night vision (IR)
- 1920 x 1080, 30 fps
- 2.8mm fixed lens
- H.265 video compression
- Motion detection supported



TECHNICAL SPECIFICATIONS

CAMERA

Image Sensor: 1/2 8" Progressive Scan CMOS

Shutter Speed: 1/3 s to 3/1000,000 s

Day & Night: IR Cut Filter

NETWORK

Alarm Trigger: Motion detection

Protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

IR

IR Range: 30m

Wave length: 850nm

ALERT, WARNING & NOTIFICATION

Written and illuminated warning through LCD (*1)

Email (via management software)

SMS and Phone Call (through SMS Module)

Audible alert via management software

Audible - Visual warning module (siren) (*2)

Sensaway Mobile App Notification

(*1) It works with BirSens modules.

(*2) It works with compatible BirSens modules & Siren.

SENSAWAY LICENSED IP CAMERA

IMAGE

Max. Resolution: 1920 x 1080

Main Stream: 50Hz: 25fps (1920 x 1080, 1280 x 960, 1280 x 720)
60Hz: 30fps (1920 x 1080, 1280 x 960, 1280 x 720)

Sub-Stream: 50Hz: 25fps (704 x 576, 640 x 480, 352 x 288, 320 x 240)
60Hz: 30fps (704 x 480, 640 x 480, 352 x 240, 320 x 240)

Image Settings: Rotate mode, saturation, brightness, contrast, sharpness adjustable by client software or web browser

GENERAL

Operating Conditions: -30°(to +60°C (-22°F to +140°F), humidity 95 % or less (non-condensing)

Power Supply: 12 VDC \pm 25%, PoE (802, 3af, class 3)

Protection Level: IP67| IK10

Dimensions: Camera: \varnothing 111 x 82.4 mm

Weight: 600 g

LENS

Focal Length: 2.8 mm

Focus: Fixed

MONITORING & MANAGEMENT SOFTWARE

Sensaway Monitoring & Management Software



(Sample picture notification)