



LM 1000

IP Based Led Module



You can instantly monitor the values of sensors connected to Birsens environmental monitoring modules. There is an area of 4X10 characters on the screen that can be managed via the web interface. You can create the design you want with 7 different color support. Lorem ipsum



Model	IP Based Led Module LM 1000	IP Led Module & Environment Monitoring LM 1000S
Reading Data from Other BS Devices on the Network	Yes	-
Internal 3 Sensor Ports and Relay Output *	-	Yes
Connection Type	Ethernet	Ethernet
Supply	12 V / POE	12 V / POE
Functional Button	Yes	Yes

*Temperature, Humidity, Air quality and Water sensors can be connected to 3 internal sensor ports. Can be used with LM 1000S model

DIMENSIONS

Width	: 400 mm
Height	: 220 mm
Depth	: 55 mm

MOUNTING

Wall Mount

MONITORING & MANAGEMENT SOFTWARE

Sensaway Monitoring & Management Software

WEIGHT

1.100 g

ALERT, WARNING & NOTIFICATION

- Written and illuminated warning via LCD (*1)
- Email (with management software)
- SMS and Phone Call (through SMS Module)
- Audible alert via management software
- Audible - Visual warning module (siren)(*2)
- Sensaway Mobile App Notification

(*1) It works with BirSens modules.

(*2) It works with compatible BirSens modules & Siren.