

CL 1004

Cabinet Lock & Lock Systems



Should Anyone with Access Be Intervened?

It provides remote monitoring and management of cabinet doors with its rack mounted control unit.





Model	CL 1004	CL 1008	CL 1016
Lock Ports	4	8	16
External Door Sensor	8	16	32
Relay Out	2	2	2

Management Software Features

- Monotoring cabinets on a single screen.
- Defining access authorization for persons based on the cabin or even on the basis of the front-back cabin door.
- Reporting information such as who opened the lockers and for how long.
- Send alerts and notifications in unusual situations.
- Optionally, the door can be opened remotely with authorization and within the limits granted.
- Ability to copy users and privileges between locks.



TECHNICAL SPECIFICATIONS

CL 1004

DIMENSIONS

Height: 44.45mm / 1.75" / 1U

Width: 482.6mm / 19" / 1Rack / 438 mm w/o rack kit

Depth: 152.4mm / 6"/

WEIGHT

1.950g

CONNECTION & EXPANSION

4 X RJ45 Ports (RS485) Lock Connections

2 X USB Ports

2 X Relay Out

2 X RJ45 LAN Ports-Master / Slave

1 X AC Voltage plug-in

MOUNTING

Rack Mount (Supports Front & Rear Sides)

Removable Rack Kit

ACCESSORIES

Setup & User Guide (DVD)

1 X Base Sensaway Licanse

LCD SCREEN

2 Line - 16 Characters for each line

ALERT, WARNING & NOTIFICATION

Written and illuminated warning via LCD

Email (with management software)

SMS and Phone Call (through SMS Module)

Audible alert via management software

Audable - Visual warning module (siren)

NETWORK & SECURITY

10/100 Ethernet (RJ-45 connector)

Pasword Protection, IP Adress Filtering, AES 128 encrypted communication

Protocols: HTTP, TCP/IP, DHCP

ELECTRICAL & OPERATING REQUIREMENTS

-30°C, +80°C & 0 - 85 %RH Humidity

Power Supply: 220V AC

Power Supply for Lock: 12V DC / 3A

MONITORING SOFTWARE

Sensaway Management & Monitoring Software



(CABINET DOOR & LOCK MONITORING SCREEN)

