

CL 1016

Cabinet Lock & Lock Systems



Should Anyone with Access Be Intervened?

It provides remote monitoring and management of cabinet doors with a rack-mounted control unit.





Model	CL 1004	CL 1008	CL 1016
Lock Ports	4	8	16
External Door Sensor	8	16	32
Relay Out	2	2	2

Management Software Features

- Monotoring cabinets on a single screen.
- Defining access authorization for persons based on the cabin or even on the basis of the front-back cabin door.
- Reporting information such as who opened the lockers and for how long.
- Send alerts and notifications in unusual situations.
- · Optionally, the door can be opened remotely with authorization and within the limits granted.
- Ability to copy users and privileges between locks.



TECHNICAL SPECIFICATIONS

CL 1016

DIMENSIONS

Height: 44.45mm / 1.75" / 1U

Width: 482.6mm / 19" / 1Rack / 438 mm w/o rack kit

Depth: 152.4mm / 6"/

WEIGHT

1.500g

CONNECTION & EXPANSION

16 X RJ45 Ports (RS485) Lock Connections

2 X USB Ports

2 X Relay Out

2 X RJ45 LAN Ports-Master / Slave

1 X AC Voltage plug-in

MOUNTING

Rack Mount (Supports Front & Rear Sides)

Removable Rack Kit

ACCESSORIES

Setup & User Guide (DVD)

1 X Base Sensaway Licanse

LCD SCREEN

2 Line - 16 Characters for each line

ALERT, WARNING & NOTIFICATION

Written and illuminated warning via LCD

Email (with management software)

SMS and Phone Call (through SMS Module)

Audible alert via management software

Audable - Visual warning module (siren)

NETWORK & SECURITY

10/100 Ethernet (RJ-45 connector)

Pasword Protection, IP Adress Filtering, AES 128 encrypted communication

Protocols: HTTP, TCP/IP, DHCP

ELECTRICAL & OPERATING REQUIREMENTS

-30°C, +80°C & 0 - 85 %RH Humidity

Power Supply: 220V AC

Power Supply for Lock: 12V DC / 3A

MONITORING SOFTWARE

Sensaway Management & Monitoring Software

MANAGEMENT SOFTWARE

(CABINET DOOR & LOCK MONITORING SCREEN)

