

## LM 1000 S IP Based Led Module & Environment Monitoring

 $\epsilon$ 



You can instantly monitor the values of sensors connected to Birsens environmental monitoring modules. There is an area of 4X10 characters on the screen that can be managed via the web interface. You can create the design you want with 7 different color support.

Model
Reading Data from Other BS Devices on the Network
Internal 3 Sensor Ports and Relay Output *
Connection Type
Supply
Functional Button

IP Based Led Module LM 1000	
Yes	
-	
Ethernet	
12 V / POE	
Yes	

V	
IP Led Module & Environment Monitoring LM 1000S	
-	
Yes	
Ethernet	
12 V / POE	
Yes	

<sup>\*</sup>Temperature, Humidity, Air quality and Water sensors can be connected to 3 internal sensor ports. Can be used with LM 1000S mode

DIMENSIONS		
Width	: 400 mm	
Height	: 220 mm	
Depth	: 55 mm	
MOUNTING		
Wall Mount		
MONITORING & MANAGEMENT SOFTWARE		
Sensaway Monitoring & Management Software		

WEIGHT
1.100 g
ALERT, WARNING & NOTIFICATION
Written and illuminated warning via LCD (*1)
Email (with management software)
SMS and Phone Call (through SMS Module)
Audible alert via management software
Audible - Visual warning module (siren)(*2)
Sensaway Mobile App Notification

(\*1) It works with BirSens modules.

(\*2) It works with compatible BirSens modules & Siren.